

fibo intercon

Aluminium belt conveyors



Your partner in concrete solutions



Focus on flexibility and economy



Aluminium belt conveyors in belt widths of 0.8 M and 1.0 M and lengths of 8 - 14 M. Available mounted on either wheels, height-adjustable legs or a frame with draw hook. All conveyors are delivered complete with drum motor, integrated gearbox, inlet and outlet funnel, safety limit switch and lifting devices for easy transportation.

Often a belt conveyor can be transported on top of a concrete batching plant, and conveyors in lengths of more than 8 M can be folded for further reduction of transport costs.

The belt conveyors are controlled by the batching computer in the concrete batching plant.

Technical specifications

Belt widths		0.8 M	1.0 M
Lengths	M	10 - 14	8 - 12
Outlet height	M	Adjustable	Adjustable
Belt speed	M/sec	1.6	1.6
Belt rollers	M	Plastic & steel	Plastic & steel
Belt scrapers	pcs	2	2
Drum motor	kW	4	7.5
Inlet funnel	pcs	1	1
Outlet funnel	pcs	1	1

Options

Cover for protecting the concrete against e.g. dust, rain, wind etc.

2017-07-01. copyright © fibo intercon. No responsibility can be accepted for printing errors. Construction subject to change without notice. The model displayed may include optional equipment.

Representative:

fibo intercon a/s

Herningvej 4
DK-6920 Videbaek
Denmark
Phone: +45 97 17 16 66

info@fibointercon.com
www.fibointercon.com

