

# **fibo intercon**

## Cement augers



Your partner in concrete solutions



## Complete cement auger



Cement augers in the standard dimensions Ø193 and Ø219 and with lengths between 3.5 - 4.5 M. We also offer customized cement augers on request.

All cement augers are delivered complete with either flange or universal ball joint inlet, flange for butterfly valve, cylindrical outlet, inspection hatch under inlet, reduction gearbox with electric motor at inlet end, flexible hose connection and electric cable with CE plug.

The cement augers can be assembled horizontally, obliquely or vertically.

## Technical specifications

Standard models		Ø193	Ø219
Lengths	M	3.5	4.5
Capacity at 290 Rpm	tonnes/hour	40	60
Gearbox ratio	Rpm	1440/290	1440/290
Power (3 x 400 V, 50 Hz)	kW	4.0	5.5
Electric cable with CE plug	M	8	8
Inclination	Degrees	0 - 45	0 - 45
Flexible hose at outlet	MM	Ø202 x 1000	Ø225 x 1000

### Options

Counter flange, additional outlet

2016-07-01. copyright © fibo intercon. No responsibility can be accepted for printing errors. Construction subject to change without notice. The model displayed may include optional equipment.

### Representative:

#### **fibo intercon a/s**

Herningvej 4  
DK-6920 Videbaek  
Denmark  
Phone: +45 97 17 16 66

info@fibointercon.com  
www.fibointercon.com

