fibo intercon

Semi-mobile concrete batching plant F2250





Highly mobile and flexible solution

This semi-mobile batching plant can replace a small concrete factory as it can handle even larger construction projects. It is assembled on a swap load and has a capacity of 45-55 M³/hour and a cycle time of a mere 1½ - 2 minutes.

The powerful counter flow mixer is equipped with robust mixing arms, turn able mixing shovels and side scrapers providing a short cycle time and a high, uniform concrete quality. A high quality is also ensured by the integrated control system which controls and monitors all processes and connected equipment, for instance, an in-line modular silo, horizontal cement silos and/or belt conveyors. The control system is placed in the cabin for operation monitoring.

F2250 is a highly flexible and mobile solution. It takes only about one day to erect it and it does not require a cast foundation but can be placed on a level surface. The swap load system furthermore makes it easy to move the plant between building projects.

F2250 is a profitable investment which will soon pay for itself and return a profit. All wearing parts are produced in robust materials and can be replaced separately, which minimises operating costs. There is free access to all of the plant functions, facilitating daily cleaning, maintenance and service. The batching plant is delivered with a high-pressure cleaner and additive pump.

Technical specifications

Counter flow mixer

Volume (gross/net) 2250 litres
1500 litres
Capacity 45-55 M³/hour
Electric motor 75 kW
Mixing arms 2 pcs
Mixing shovels 4 pcs
Side scrapers 1 pc
Weighing accuracy +/- 0.5 %

Power

3 x 400 Volts, 50 Hz Prime power 200 KVA

Pre-weighing of cement

Load cells 3 x 2000 kg

Water tank

Volume 8000 litres

Control system

Batching computer
Thermal printer
PC interface
Dosing accuracy
Recipes
Language version
Siemens
Included
Possible
Possible
25 pcs
As desired

Other features

Additive pump 2 pcs
Air compressor 1 pc
High-pressure cleaner 1 pc

Dimensions

Width 2.50 M Height 2.65 M Length 8.8 M Total weight 10,400 kg

Options

- · Hydraulic legs
- Generating set
- External lighting

Equipment

May be combined with, for instance, belt conveyors, horizontal cement silos and in-line modular silos.

2016-07-01. copyright © fibo intercon. No responsibility can be accepted for printing errors. Construction subject to change without notice. The model displayed may include optional equipment.

Representative:

fibo intercon a/s

Herningvej 4 DK-6920 Videbaek Denmark Phone: +45 97 17 16 66 info@fibointercon.com www.fibointercon.com

