

fibo intercon

Insulated belt conveyor 1 x 14 M



Your partner in concrete solutions



For concrete production at temperatures down to - 40 °C



Belt conveyor specially developed for fibo intercon's winter plant with a belt width of 1.0 M and a length of 14 M.

The conveyor is delivered complete with drum motor, steel rollers, gearbox, safety limit switch, inlet and outlet funnel. It is covered with steel plates and 60 MM PU insulating plates to protect the concrete from cold and rough weather.

The insulating plates can be dismantled and transported separately. The belt conveyor can furthermore be folded for easy transportation and reduced transport costs.

The belt conveyor is controlled by the batching computer in the winter plant.

Technical specifications

Model		Insulated belt conveyor
Belt width	M	1.0
Length	M	14
Outlet height	M	Adjustable
Belt speed	M/sec	1.6
Belt rollers	M	Steel
Belt scrapers	pcs	2
Drum motor	kW	7.5
Inlet funnel	pcs	1
Outlet funnel	pcs	1
Insulation	Type	60 MM PU insulating plates (dismountable)

2016-07-01. copyright © fibo intercon. No responsibility can be accepted for printing errors. Construction subject to change without notice. The model displayed may include optional equipment.

Representative:

fibo intercon a/s

Herningvej 4
DK-6920 Videbaek
Denmark
Phone: +45 97 17 16 66

info@fibointercon.com
www.fibointercon.com

