fibo intercon

Pump container for premixed mortar

Your partner in concrete solutions

fibo intercon

A compact solution for flooring

Inside view displaying the mixing and pumping equipment

The draw hook makes it easy to move and transport the plant

Highly flexible and mobile solution

This pump container is designed for mixing and pumping premixed mortar. The end product is a high-quality, self-compacting material ideal for flooring.

The pump container is assembled on a fully insulated 20 foot container frame providing it with a unique flexibility. The computer controlled weighing system and the exact water dosing ensure that premixed mortar of a high, homogeneous quality can be produced continuously and that the material consumption is fully documented.

Advantages

- The insulated container frame reduces noise and makes it possible to use the plant all year round
- Generator operation, requiring no external energy connection
- Doors and hatches on the plant sides provide facilitates plant operation, cleaning and servicing
- Can quickly be made ready for operation
- User-friendly operating system
- Low operating and maintenance costs

The standard pump container is delivered with:

Mixer, generating set, aggregate silo with top hatch for filling with big bag or the like, weighing hoppers, augers, vibrators, hose drums, safety equipment, high-pressure cleaner, screw pump, weighing equipment, water hose, water connection, flow meter for water dosing, external coupling for lighting, heating etc., PLC computer with touch screen and weighing electronics.

Technical specifications

Pump capacity	10 M^3/hour
Pump height	40 - 60 M
Generator	60 kWA
Aggregate silo	5 M^3
Water tank	1 M^3
Weighing hoppers	2 x 150 L
Weight	8000 kg

Options

- Wireless data transfer to PC
- Remote control for top hatch
- Remote control for start/stop of pump
- Measurement of mass temperature
- Measurement of floor temperature
- Water heater

2011-01-18. copyright © fibo intercon. No responsibility can be accepted for printing errors. Construction subject to change without notice. The model displayed may include optional equipment.

Representative:

fibo intercon a/s

Herningvej 4
DK-6920 Videbaek
Denmark
Phone: +45 97 17 16 66
Fax: +45 97 17 11 75

info@fibointercon.com
www.fibointercon.com

fibo intercon